



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/789,540	02/27/2004	Eric Sandstrom	DKT 03066A (BWI-00084)	9464
68945 7590 01/31/2008 WARN, HOFFMANN, MILLER & OZGA, P.C. P.O. BOX 70098 ROCHESTER HILLS, MI 48307			EXAMINER KISWANTO, NICHOLAS	
			ART UNIT 3664	PAPER NUMBER
			MAIL DATE 01/31/2008	DELIVERY MODE PAPER

**Please find below and/or attached an Office communication concerning this application or proceeding.**

The time period for reply, if any, is set in the attached communication.

<b>Office Action Summary</b>	<b>Application No.</b> 10/789,540	<b>Applicant(s)</b> SANDSTROM, ERIC	
	<b>Examiner</b> NICHOLAS KISWANTO	<b>Art Unit</b> 3664	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

### Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

### Status

- 1) ☐ Responsive to communication(s) filed on \_\_\_\_.
- 2a) ☒ This action is **FINAL**.                      2b) ☐ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

### Disposition of Claims

- 4) ☒ Claim(s) 1-21 is/are pending in the application.
- 4a) Of the above claim(s) \_\_\_\_ is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_ is/are allowed.
- 6) ☐ Claim(s) 1-21 is/are rejected.
- 7) ☐ Claim(s) \_\_\_\_ is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_ are subject to restriction and/or election requirement.

### Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 27 February 2004 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.  
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

### Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All    b) ☐ Some \*    c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
  2. ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_.
  3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

\* See the attached detailed Office action for a list of the certified copies not received.

### Attachment(s)

- |  |   |
|--|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892)                                | 4) <input type="checkbox"/> Interview Summary (PTO-413)<br>Paper No(s)/Mail Date. ____. |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948)                       | 5) <input type="checkbox"/> Notice of Informal Patent Application                       |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08)<br>Paper No(s)/Mail Date ____. | 6) <input type="checkbox"/> Other: ____.  |

## DETAILED ACTION

Final Rejection sent on 1/25/2008 and this instant action **BOTH** requires responses.

The statutory period for responding to both Office Actions has been reset. Applicant is given three months from the date of this Office Action to response to both Actions.

### *Claim Rejections - 35 USC § 103*

1. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

2. Claims 1 – 4, 6 –15 are rejected under 35 U.S.C. 103(a) as being unpatentable over Kurihara (6,449,547), which henceforth shall be referred to as “Kurihara/547”, in view of Ishii et al. (6,751,542), which henceforth shall be referred to as “Ishii/542”, further in view of Yutkowitz(6,865,499), which henceforth shall be referred to as “Yutkowitz/499”.

As to claim 1, Kurihara/547 shows method of calibrating an electrohydraulic control system that provides an output response in response to an input current (col 2, line 26 – 37), said method comprising: identifying a characteristic equation of the electrohydraulic system, said characteristic equation including a plurality of coefficients (col 3, line 23 – 42); measuring the

output response of the electrohydraulic system (col 5, line 31 – 44), and identifying the coefficients in the characteristic equation from the output response measurements. (col 5, line 31 – 44).

Kurihara/547 does not show applying a plurality of currents to the electrohydraulic system and measuring the output response of the electrohydraulic system for each of the plurality of currents.

Ishii/542 shows a plurality of currents applied to an electrohydraulic system (col 7, line 34 – 38) and measuring the output response of the electrohydraulic system for each of the plurality of currents (col 7, line 34 – 38). Ishii/542 teaches that measuring the output response of a plurality of currents leads to a hysteresis characteristic being exhibited between the current and the output liquid pressure. Hence, a transmission map is generated, the map being an average output liquid pressure value at each current value from a static characteristic (col 2, line 29 – 34).

It would have been obvious to one of ordinary skill in the art to modify the invention of Kurihara/547 by adding a plurality of currents being applied to the electrohydraulic system and measuring the output in order to generate a transmission map (col 2, line 29 – 34), as taught by Ishii/542.

Kurihara/547 does not show that applying a plurality of currents to the electrohydraulic system includes applying a plurality of different currents.

Ishii/542 shows an electrohydraulic system where applying a plurality of currents includes applying a plurality of different currents (col 7, line 34 – 38).

Ishii/542 teaches that measuring the output response of a plurality of currents leads to a hysteresis characteristic being exhibited between the current and the output liquid pressure. Hence, a transmission map is generated, the map being an average output liquid pressure value at each current value from a static characteristic (col 2, line 29 – 34).

It would have been obvious to one of ordinary skill in the art to modify the invention of Kurihara/547 by adding a plurality of currents being applied to the electrohydraulic system and measuring the output in order to generate transmission map (col 2, line 29 – 34), as taught by Ishii/542.

Kurihara/547 does not show flashing the coefficients in a memory.

Ishii/542 shows wherein the method comprises flashing the coefficients in a memory (col 8, line 5 - 6).

It would have been obvious to one of ordinary skill in the art to modify Kurihara/547's invention by adding wherein the method comprises flashing the coefficients in a memory in order to preserve the data for future use, as taught by Ishii/542.

Kurihara/547 and Ishii/542 still do not show the electrohydraulic system coupled to a test stand.

Yutkowitz/499 shows an electrohydraulic system coupled to a test stand (Fig. 1).

It would have been obvious to one of ordinary skill in the art to modify the invention taught by Kurihara/547 and Ishii/542 by coupling the electrohydraulic

system to a test stand in order to extract the values from the electrohydraulic system when a plurality of currents are applied to it, as taught by Yutkowitz/499.

As to claim 2, Kurihara/547 further shows wherein identifying the coefficients in the characteristic equation from the output response measurements includes employing a curve fitting function (col 6, line 42 – 47).

As to claim 3, Kurihara/547 further shows wherein identifying the coefficients in the characteristic equation from the output response measurements includes employing a least squares fitting function. (6449547, 6, 42 – 47)

As to claim 6, Kurihara/547 does not show an electrohydraulic system that includes a proportional solenoid and a hydraulic valve, wherein applying a plurality of currents to the electrohydraulic system includes applying a plurality of currents to the proportional solenoid.

Ishii/542 shows an electrohydraulic system that includes a proportional solenoid (col 8, line 5 – 6) and a hydraulic valve (col 5, line 31 – 43), wherein applying a plurality of currents to the electrohydraulic system includes applying a plurality of currents to the proportional solenoid (col 7, line 34 - 38).

Ishii/542 teaches that measuring the output response of a plurality of currents leads to a hysteresis characteristic being exhibited between the current

and the output liquid pressure. Hence, a transmission map is generated, the map being an average output liquid pressure value at each current value from a static characteristic (col 2, line 29 – 34).

It would have been obvious to one of ordinary skill in the art to modify the invention of Kurihara/547 by adding a plurality of currents being applied to the electrohydraulic system and measuring the output in order to generate a transmission map (col 2, line 29 – 34), as taught by Ishii/542.

As to claim 7, Kurihara/547 further shows an electrohydraulic system that is employed in an automatic transmission (col 2, line 39 – 40).

As to claim 8, Kurihara/547 further shows an electrohydraulic system that is employed in a pressure regulation system or a flow regulation system used for controlling functions in the automatic transmission (col 10, line 35 – 38).

As to claim 9, Kurihara/547 further shows an electrohydraulic system that includes an integrated transmission control unit (TCU) (col 4, line 20 – 21).

As to claim 10, Kurihara/547 further shows the output response of an electrohydraulic system is selected from the group consisting of pressure and fluid flow (col 10, line 35 – 38).

As to claim 12, Kurihara/547 shows a method of calibrating an electrohydraulic system employed in an automatic transmission (col 10, line 35 – 38), said electrohydraulic system providing an output response in response to an input current (col 5, line 31 – 44), said method comprising: identifying a characteristic equation of the electrohydraulic system, said characteristic equation including a plurality of coefficients (col 3, line 23 – 42); measuring the output response of the electrohydraulic system for a current applied to it (col 5, line 31 – 44); and identifying the coefficients of the characteristic equation from the output response measurements (col 5, line 31 – 44), wherein identifying the coefficients in the characteristic equation from the output response measurements includes employing a curve fitting function (col 6, line 42 – 47).

Kurihara/547 does not show that the electrohydraulic system comprises a proportional solenoid, a hydraulic valve, solenoid drive electronics, and a plurality of currents applied to the solenoid controlling the valve.

Ishii/542 shows an electrohydraulic system comprising a proportional solenoid (col 8, line 5 – 6), a hydraulic valve (col 5, line 32 – 33), solenoid drive electronics (col 8, line 5 – 6), and a plurality of currents applied to the solenoid controlling the valve (col 7, line 34 – 38). Ishii/542 teaches that measuring the output response of a plurality of currents leads to a hysteresis characteristic being exhibited between the current and the output liquid pressure. Hence, a transmission map is generated, the map being an average output liquid pressure value at each current value from a static characteristic (col 2, line 29 – 34).



It would have been obvious to one of ordinary skill in the art to modify the invention of Kurihara/547 by adding a plurality of currents being applied to the electrohydraulic system and measuring the output in order to generate a transmission map (col 2, line 29 – 34), as taught by Ishii/542.

Kurihara/547 and Ishii/542 still does not show the electrohydraulic system coupled to a test stand.

Yutkowitz/499 shows an electrohydraulic system coupled to a test stand (Fig. 1).

It would have been obvious to one of ordinary skill in the art to modify the invention taught by Kurihara/547 and Ishii/542 by coupling the electrohydraulic system to a test stand in order to extract the values from the electrohydraulic system when a plurality of currents are applied to it, as taught by Yutkowitz/499.

As to claim 13, Kurihara/547 further shows the electrohydraulic system employed in a pressure regulation system or a flow regulation system used for controlling functions in the automatic transmission (col 10, line 35 – 38).

As to claim 14, Kurihara/547 further shows where the step of identifying the coefficients in the characteristic equation from the output response measurements includes employing a least squares fitting function (col 6, line 42 – 47).

As to claim 15, Kurihara/547 further shows the output response of the hydroelectric system is selected from the group consisting of pressure and fluid flow (col 10, line 35 – 38).

3. Claims 16 – 21 are rejected under 35 U.S.C. 103(a) as being unpatentable over Kurihara/547 in view of Ishii/542.

As to claim 16, Kurihara/547 shows an electrohydraulic system comprising: a device for determining a characteristic equation of the electrohydraulic system, said characteristic equation including a plurality of coefficients (col 3, line 23 – 42); a device for measuring an output response of the electrohydraulic system from a current (col 5, line 31 – 44); and a device for determining the coefficients in the characteristic equation from the output response measurement (col 5, line 31 – 44).

Kurihara/547 does not show the electrohydraulic device comprising of a device for applying a plurality of currents to a proportional solenoid in the system.

Ishii/542 shows a device for applying a plurality of currents to a proportional solenoid in the system (col 7, line 34 - 38).

Ishii/542 teaches that measuring the output response of a plurality of currents leads to a hysteresis characteristic being exhibited between the current and the output liquid pressure. Hence, a transmission map is generated, the

map being an average output liquid pressure value at each current value from a static characteristic (col 2, line 29 – 34).

It would have been obvious to one of ordinary skill in the art to modify the invention of Kurihara/547 by adding a plurality of currents being applied to the electrohydraulic system and measuring the output in order to generate a transmission map (col 2, line 29 – 34), as taught by Ishii/542.

Kurihara/547 does not show a memory for storing the coefficients from the characteristic equation.

Ishii/542 shows an electrohydraulic system with a memory for storing coefficients (col 8, line 5 - 6).

It would have been obvious to one of ordinary skill in the art to modify Kurihara/547's invention by adding wherein the method comprises flashing the coefficients in a memory in order to preserve the data for future use, as taught by Ishii/542.

As to claim 17, Kurihara/547 further shows the device that determines the coefficients in the characteristic equation from the output response measurement employs a curve fitting function (col 6, line 42 – 47).

As to claim 19, Kurihara/547 shows that the electrohydraulic system is employed in an automatic transmission (col 10, line 35 – 38).

As to claim 20, Kurihara/547 shows that the electrohydraulic system is employed in a pressure regulation system or a flow regulation system used for controlling functions in the automatic transmission (col 10, line 35 – 38).

As to claim 21, Kurihara/547 shows where the output response of the electrohydraulic system is selected from the group consisting of pressure and fluid flow (col 10, line 35 – 38).

4. Claim 5 is rejected under 35 U.S.C. 103(a) as being unpatentable over Kurihara/547, in view of Ishii/542, further in view of Yutkowitz/499, further in view of Tsutsui et al. (5,782,711), which henceforth shall be referred to as “Tsutsui/711”.

As to claim 5, Kurihara/547, Ishii/542, and Yutkowitz/499 disclose all elements per claimed invention as explained in paragraph 2 above.

However, Kurihara/547, Ishii/542 et al, and Yutkowitz/499 do not show the electrohydraulic system hard-coding the characteristic equation into control software.

Tsutsui/711 shows an electrohydraulic system that uses a commonly well-known method in the art of hard-coding the characteristic equation into control software (col 4, line 14 – 16).

It would have been obvious to one of ordinary skill in the art to modify the invention of Kurihara/547, Ishii/542, and Yutkowitz/499 by using the commonly

well-known method in the art of hard-coding the characteristic equation into control software as demonstrated by Tsutsui/711.

***Response to Amendment***

4. The exhibits filed on 10/29/2007 under 37 CFR 1.131 has been considered but is ineffective to overcome the Ishii et al. (6,751,542).

Applicant's affidavit stating reduction to practice occurred prior to 3/28/03 with some evidence is not sufficient. Please see MPEP 715.07 III: "A conception of an invention, though evidenced by disclosure, drawings, and even a model, is not a complete invention under the patent laws, and confers no rights on an inventor, and has no effect on a subsequently granted patent to another, unless the inventor follows it with reasonable diligence by some other act, such as an actual reduction to practice or filing an application for a patent."

Further, regarding applicant's second affidavit argument, there is insufficient showing of diligence. Although applicants have provided emails and slides there is insufficient showing of when events happened, see MPEP 715.07(a). Diligence must be shown from just before 3/28/03 to the filing of applicant's provisional, 4/11/03.

***Response to Arguments***

5. Applicant's arguments filed 10/29/2007 have been fully considered but they are not persuasive.

Applicant argues that "The values of output are determined by horse power demand and vehicle speed. The coefficients determined are for control of a variable displacement engine and not a hydraulic valve as in Applicant's invention."

Said argument is not persuasive due to horse power demand and vehicle speed being electrical currents within a vehicle's electrohydraulic control system. Further, while Kurihara/547 may determine coefficients for control of a variable displacement engine, it also determines coefficients for an automatic transmission (electrohydraulic control system), see column 9, lines 33 - 36.

### ***Conclusion***

6. The prior art made of record and not relied upon is considered pertinent to applicant's disclosure.

Iwawa et al. (5,487,003) shows a method to provide data output from a set of input data, using least means square to achieve its results.

Boger et al. (2001/0037670) shows a valve positioner system that uses a process of discovering coefficients in a characteristic equation.

Funk, Sr. et al. (6,070,485) shows a solenoid shifter.

Todd et al. (7,231,317) shows a control system that has a plurality of currents applied to it and finds coefficients of various equations pertaining to the system.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to NICHOLAS KISWANTO whose telephone number is (571)270-3269. The examiner can normally be reached on Monday - Friday, 8AM - 5PM, EST.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Khoi Tran, can be reached on (571) 272-6919. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300. Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

Nicholas Kiswanto  
January 28, 2008  
/Khoi H Tran/  
Supervisory Patent Examiner, Art Unit 3664